

Variant: DP83TC813  
 Generated: 5/27/2024 12:50 PM  
 TID #: N/A



TIDA-020073 REV E1 Bill of Materials

Item #	Designator	Quantity	Value	PartNumber	Manufacturer	Description	PackageReference
1	IPCB	1		TIDA-020073	Any	Printed Circuit Board	
2	3V3, 3V3IO, 5V0, 12V0_GND, INH	7		TSW-101-07-G-S	Samtec	Header, 100mil, 1pos, Gold, TH	Testpoint
3	C1, C12, C13, C14, C21, C26, C27, C36, C37, C49, C52	11	0.1uF	C1005X5R1H104K050BB	TDK	CAP, CERM, 0.1 uF, 50 V, +/- 10%, X5R, 0402	0402
4	C3, C4, C51	3	10uF	GRM155R61A106ME11	MuRata	CAP, CERM, 10 uF, 10 V, +/- 20%, X5R, 0402	0402
5	C7, C8, C9	3	2.2uF	C1005X5R1V225K050BC	TDK	CAP, CERM, 2.2 uF, 35 V, +/- 10%, X5R, 0402	0402
6	C17, C18, C19, C28, C29, C54	6	0.01uF	GRM155R61C103KA01D	MuRata	CAP, CERM, 0.01 uF, 16 V, +/- 10%, X5R, 0402	0402
7	C22, C50	2	10uF	C1608X5R1E106M080AC	TDK	CAP, CERM, 10 uF, 25 V, +/- 20%, X5R, 0603	0603
8	C30, C31	2	27pF	C0402C270J5GACTU	Kemet	CAP, CERM, 27 pF, 50 V, +/- 5%, C0G/NP0, 0402	0402
9	C38, C39	2	4700pF	GRM31BR73A472KW01L	MuRata	CAP, CERM, 4700 pF, 1000 V, +/- 10%, X7R, 1206	1206
10	C44	1	47uF	C2012X5R1A476M125AC	TDK	CAP, CERM, 47 uF, 10 V, +/- 20%, X5R, 0805	0805
11	D1, D3, D4, D8, D9	5	Green	APT2012LZGCK	Kingbright	LED, Green, SMD	LED_0805
12	D10	1	Red	150060RS75000	Würth Elektronik	LED, Red, SMD	LED_0603
13	FID1, FID2, FID3, FID4, FID5, FID6	6		N/A	N/A	Fiducial mark. There is nothing to buy or mount.	N/A
14	J1	1		1714505106	Molex	Conn Shrouded RCP 60 POS 0.8mm Solder ST SMD Emboss T/R	CONN_RCPT60
15	J2	1		9-2304372-1	TE Connectivity	Header(shrouded), 2x1, R/A, TH	Header(shrouded), 2x1, R/A, TH
16	J3, J4, J5, J6, J19	5		TSW-102-07-G-S	Samtec	Header, 100mil, 2x1, Gold, TH	2x1 Header
17	J16, J18	2		TSW-103-07-G-S	Samtec	Header, 100mil, 3x1, Gold, TH	3x1 Header
18	L1	1		DLW32MH201XK2	Murata	200uH @ 100kHz 2 Line Common Mode Choke Surface Mount 70mA DCR 4.8 Ohm	1210
19	L2	1			Würth Elektronik	WE-MAPI SMT Power Inductor, size 4020, 2.2uH, 4.7A, 35mOhm	
20	L3	1		ADL32VHR-180M	TDK	Differential Mode Choke 18uH 370mA 0.84Ohm 3.2x2.5x2.5mm SMT	SMT_3MM2_2MM5
21	L4, L5	2	600 ohm	BLM18KG601SN1D	MuRata	Ferrite Bead, 600 ohm @ 100 MHz, 1.3 A, 0603	0603
22	L6	1		BLM18KG102SH1D	Murata	1 kOhms @ 100MHz 1 Power Line Ferrite Bead 0603 (1608 Metric) 1A 200mOhm	0603
23	LBL1	1		THT-14-423-10	Brady	Thermal Transfer Printable Labels, 0.650" W x 0.200" H - 10,000 per roll	PCB Label 0.650 x 0.200 inch
24	R1, R2, R3, R6	4	10.0k	RT0402BRD0710KL	Yageo America	RES, 10.0 k, .1%, .0625 W, 0402	0402
25	R5, R7, R8, R9, R10, R11, R13, R14, R15, R17, R19, R43, R44, R45, R46, R65, R68, R72	18	0	CRCW04020000Z0ED	Vishay-Dale	RES, 0, 5%, 0.063 W, AEC-Q200 Grade 0, 0402	0402
26	R12, R26, R41, R62, R63, R64	6	2.49k	CRCW04022K49FKED	Vishay-Dale	RES, 2.49 k, 1%, 0.063 W, AEC-Q200 Grade 0, 0402	0402
27	R16	1	0	CRCW06030000Z0EAC	Vishay	CRCW Series 0603 0.1 W 0 Ohm Jumper Surface Mount Thick Film Chip Resistor	0603
28	R18	1	100k	CRCW0402100KFKED	Vishay-Dale	RES, 100 k, 1%, 0.063 W, AEC-Q200 Grade 0, 0402	0402
29	R20	1	52.3k	CRCW040252K3FKED	Vishay-Dale	RES, 52.3 k, 1%, 0.063 W, AEC-Q200 Grade 0, 0402	0402
30	R22, R24	2	4.53k	CRCW04024K53FKED	Vishay-Dale	RES, 4.53 k, 1%, 0.063 W, AEC-Q200 Grade 0, 0402	0402
31	R27, R28, R32, R36	4	470	CRCW0402470RJNED	Vishay-Dale	RES, 470, 5%, 0.063 W, AEC-Q200 Grade 0, 0402	0402
32	R38	1	1.00Meg	ERJ-2RKF1004X	Panasonic	RES, 1.00 M, 1%, 0.1 W, 0402	0402
33	R53, R54	2	1.00k	ERJ-P06F1001V	Panasonic	RES, 1.00 k, 1%, 0.25 W, 0805	0805
34	R55	1	100k	RT0805BRD07100KL	Yageo America	RES, 100 k, 0.1%, 0.125 W, 0805	0805
35	R56	1	1.0Meg	CRCW12061M00JNEA	Vishay-Dale	RES, 1.0 M, 5%, 0.25 W, AEC-Q200 Grade 0, 1206	1206
36	R78	1	100	CRCW0402100RKFED	Vishay-Dale	RES, 100, 1%, 0.063 W, AEC-Q200 Grade 0, 0402	0402
37	S1	1		KSR221GLFS	C&K Components	Switch, Normally open, 2.3N force, 200k operations, SMD	KSR
38	SH-J1, SH-J2, SH-J3, SH-J4, SH-J5, SH-J6, SH-J8	7	1x2	SPC02SYAN	Sullins Connector Solutions	Shunt, 100mil, Flash Gold, Black	Closed Top 100mil Shunt
39	U2	1		DP83TC813	Texas Instruments	TC-10 Compliant 100Base-T1 Automotive Ethernet PHY	VQFN28
40	U4	1		TPS3838K33QDBVRQ1	Texas Instruments	Nanopower Supervisory Circuits for Automotive, DBV0005A (SOT-23-5)	DBV0005A
41	U5	1		TPS629210QDRLRQ1	Texas Instruments	3-V to 17-V, Synchronous Buck Converters in 1.6 mm x 2.1 mm SOT583 Package	FCSOT8
42	U6	1		TPD2E2U06QDCKRQ1	Texas Instruments	Automotive Dual-Channel High-Speed ESD Protection Device, DCK0003A (SOT-SC70-3)	DCK0003A
43	U12	1		TPS7B8233DRV-Q1	Texas Instruments	300-mA High-Voltage Ultralow-IQ Low-Dropout Regulator	WSO6
44	Y1	1		ABM8AIG-25.000MHZ-12-2Z-T3	Abracon Corporation	Crystal, 25 MHz, 12pF, AEC-Q200 Grade 1, SMD	3.2x2.5mm
45	C56	0	0.1uF	C1005X5R1H104K050BB	TDK	CAP, CERM, 0.1 uF, 50 V, +/- 10%, X5R, 0402	0402
46	D5, D6	0		EZAEG3W11AV	Panasonic	Diode, TVS, Bi, AEC-Q101, 0603	0603
47	H2, H3, H4	0		NY PMS 440 0025 PH	B&F Fastener Supply	Machine Screw, Round, #4-40 x 1/4, Nylon, Philips panhead	Screw
48	R4	0	10.0k	RT0402BRD0710KL	Yageo America	RES, 10.0 k, .1%, .0625 W, 0402	0402
49	R21	0	0	CRCW04020000Z0ED	Vishay-Dale	RES, 0, 5%, 0.063 W, AEC-Q200 Grade 0, 0402	0402
50	R25	0	249k	CRCW0402249KFKED	Vishay-Dale	RES, 249 k, 1%, 0.063 W, AEC-Q200 Grade 0, 0402	0402
51	R34, R39	0	2.49k	CRCW04022K49FKED	Vishay-Dale	RES, 2.49 k, 1%, 0.063 W, AEC-Q200 Grade 0, 0402	0402
52	U1	0		CAT24C256WI-GT3	ON Semiconductor	256 kb I2C CMOS Serial EEPROM, SOIC-8	SOIC-8
53	Y2	0		CDC6CE02500CJLE	Texas Instruments	Low Jitter, Low Power, LVCMOS Output, BAW Oscillator	VSON4

## IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATA SHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, regulatory or other requirements.

These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you will fully indemnify TI and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to [TI's Terms of Sale](#) or other applicable terms available either on [ti.com](https://www.ti.com) or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products.

TI objects to and rejects any additional or different terms you may have proposed.

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265  
Copyright © 2024, Texas Instruments Incorporated